

5mm SMD 3535 RGBW Addressable LED strip 60LEDs/m



◆ Product Description:

This SMD3535 RGBW addressable led strip with 60 LEDs & 60Pixels per meter, each LED can be controlled individually

Compared with RGB led strip , there are one more white color, more lighting effects for us

The color(CCT) of white can be warm white, nature white, pure white and cold white

Colors are rich and varied, it can realize different changing effects by the controller

5mm width, suitable for installation in narrow space

Easy and free cutting and welding: you can cut and weld all kinds of length according to the above cutting mark




◆ Product Datasheet

Product Number	S005060DA4SA1
Operating Voltage	DC5V
Power/m	13W
SMD Type	SMD 3535
LED Qty/m	60
Cutting Length	16.66mm/1LED
Color	RGBW:3000K/4000K/6500K
Luminance/m	R:41 G:128 B:32 W:323lm
Wavelength	R:620-625 G:520-525 B:460-465nm
Ra	80
Pixel/M	60
Material	FPC
Control	SPI/SK6812
Beam Angle	120°
Size (mm)	5000x5mm
IP Rating	IP20/IP65
Operation Temperature	- 25 ~ 60°C

Remarks:

- 1.The above parameters were tested according to integrating sphere TM-30-15.
- 2.The output data is based on IP20 and one merter.
- 3.The data such as power etc, ±15% tolerance is normal.
- 4.IP protection process causes changes in size, CCT and luminous flux.

Outline Dimension (unit:mm)



Wiring diagram



IP Rating



Note: The parameters are subject to change without notice!

◆ Related products:




Power supply
LRS-350-12




SD card controller
K-1000C


◆ Installation method:




Can be cut




Tear off the 3M adhesive as need




Folding pads



Excessive bending




Bend to LED




Reverse Strip

Distortion(Wrong)

◆ Product packaging



Reel



Antistatic bag

