

Side emitting digital RGB COB LED Strip – 840LEDs /m



Product Description:

- High density, the light is even and soft
- High efficiency, remarkable energy saving effect
- Double layer PCB, balancing voltage drop, heat dissipation and flexibility.
- Chip longitudinal distribution, high reliability;
- Standard 5M/roll, length can be customized
- The side emitting COB LED strip comes out under the demand of edge lighting.



Product Datasheet


Product Number	S010840ZC3SF(C)
Operating Voltage	DC24V
Power/m	13W
SMD Type	COB
LED Qty/m	840
Cutting Length	100mm
Color	RGB
Pixel/m	10
Luminance/m	R: 54.5 G:178 B:37 lm
Wavelength	R:615-630 G:520-535 B:450-460 nm
Control	SPI-WS2811
Beam Angle	120°
Size	5000x10mm
IP Rate	IP20/IP65
Operation Temperature	- 25 ~ 60°C

Remarks:


- 1.The above parameters were tested according to integrating sphere TM-30-15.
- 2.The output data is based on IP20 and one merter.
- 3.The data such as power etc, ±15% tolerance is normal.
- 4.IP protection process causes changes in size, CCT and luminous flux.

Outline Dimension (unit:mm)

DC24V



Wiring diagram



IP Rate



◆ Related products




Power supply
LRS-350-24



K-1000C


◆ Schematic diagram of maximum bending prevention



Bending diameter $\geq 60\text{mm}$



Correct bending method



Wrong method

◆ Product packaging



Reel



Antistatic bag

